

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 1046.1227/JDH

First Named Inventor or Application Identifier:

Yutaka SAITO

Express Mail Label No.

**APPLICATION ELEMENTS**

See MPEP chapter 600 concerning utility patent application contents.

**ADDRESS TO: Assistant Commissioner for Patents**  
**Box Patent Application**  
**Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract ..... [ Total Pages: 21]
3. ☒ Drawing(s) (35 USC 113) ..... [ Total Sheets: 3]
4. ☒ Oath or Declaration ..... [ Total Pages: 3]  
 a. ☒ Newly executed (original or copy)  
 b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)  
 i. ☐ **DELETION OF INVENTOR(S)**  
 Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)  
 The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)  
 a. ☐ Computer Readable Copy  
 b. ☐ Paper Copy (identical to computer copy)  
 c. ☐ Statement verifying identity of above copies

**ACCOMPANYING APPLICATION PARTS**

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [ ] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449[X] Copies of IDS Citations (2)
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [ ] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

**17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:**[ ] Continuation [ ] Divisional [ ] Continuation-in-part (CIP) of prior application No:      /     **18. CORRESPONDENCE ADDRESS**

21171

PATENT TRADEMARK OFFICE

Staas &amp; Halsey

**NEW APPLICATION  
FEE TRANSMITTAL**

Attorney Docket No. 1046.1227/JDH

Application Number To be assigned

Filing Date December 14, 2000

AMOUNT ENCLOSED \$910.00

First Named Inventor Yutaka SAITO

**FEE CALCULATION** (fees effective 10/1/00)

| CLAIMS   | (1) FOR | (2) NUMBER FILED | (3) NUMBER EXTRA | (4) RATE                      | (5) CALCULATIONS |
|--|---------|------------------|------------------|-------------------------------|------------------|
| TOTAL CLAIMS   | 11      | - 20 =           | 0                | X \$ 18.00 =                  | \$ 0.00          |
| INDEPENDENT CLAIMS   | 5       | - 3 =            | 2                | X \$ 80.00 =                  | 160.00           |
| MULTIPLE DEPENDENT CLAIMS (any number; if applicable)                            |         |                  |                  | + \$260.00 =                  | 0.00             |
|  |         |                  |                  | <b>BASIC FILING FEE</b>       | 710.00           |
|  |         |                  |                  | Total of above Calculations = | \$ 870.00        |
| Surcharge for late filing fee, Statement or Power of Attorney (\$130.00)         |         |                  |                  |                               | +                |
| Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28).           |         |                  |                  |                               | -                |
|  |         |                  |                  | <b>TOTAL FILING FEE =</b>     | \$ 870.00        |
| Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d)) |         |                  |                  |                               | +                |
| Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1))                           |         |                  |                  |                               | 40.00            |
|  |         |                  |                  | <b>TOTAL FEES DUE =</b>       | \$ 910.00        |

**METHOD OF PAYMENT**

- ☒ Check enclosed as payment.
- ☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.
- ☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

**GENERAL AUTHORIZATION**

- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No.

19-3935

Deposit Account Name

STAAS &amp; HALSEY LLP

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(d)) to maintain pendency hereof or of any such related application.

**SUBMITTED BY: STAAS & HALSEY LLP**

Typed Name

James D. Halsey, Jr.

Reg. No.

22,729

Signature

Date

December 14, 2000

IMAGE PHOTOGRAPHING SYSTEM HAVING TIMER FUNCTION, AND MEDIUM

BACKGROUND OF THE INVENTION

5 The present invention relates to an image photographing system.

10 Timer photographing in an image photographing system such as a camera is defined as a function of performing photography after a predetermined time has elapsed after a user had started the timer photographing. For executing this function, a conventional image photographing system has a button for the timer photographing separately from a photographing button for instructing normal photographing.

15 If the photographing button and the timer photographing button are thus separately constructed, a larger area is needed for mounting these buttons. This kind of construction has been an obstacle against downsizing the image photographing system. Further, the timer photographing button is different from the normal photographing button, and therefore the number of components of the image photographing system increases.

20

SUMMARY OF THE INVENTION

25 It is a primary object of the present invention, which was devised to obviate the problems inherent in the prior art described above, to provide an image photographing system in which one button is used in common for a function of prompt photographing and a function of photographing after a predetermined time has elapsed.

09737588-121800

It is another object of the present invention to provide an image photographing system capable of executing a timer photographing function and reducing the number of components with a simple construction.

5 To accomplish the above objects, according to one aspect of the present invention, a processing system comprises a timer, and a control unit for monitoring a button for instructing an execution of an image photographing process, starting up the timer if the button is depressed continuously for a predetermined  
10 time or longer, and executing the image photographing process after the timer has counted a predetermined time.

The processing system may be connected to an image photographing system, whereby the image photographing process is controlled. The connection may be provided with wireless  
15 method. Further, this processing system may be incorporated into the image photographing system, whereby the image photographing process is controlled.

The control unit, if a depressing time of the button is less than the predetermined time, may execute the image  
20 photographing process immediately after releasing the button from be depressed.

This button may be provided on a connectable/disconnectable image acquisition device. Further, the button may be an object displayed on a display device.

25 According to another aspect of the present invention, a processing system comprises a module for detecting a depressing time of a button for instructing an execution of an image

09737588-121800

photographing process, and a module for changing a timing of executing the image photographing process after releasing the button from being depressed on the basis of the depressing time of the button.

5           According to a further aspect of the present invention, an image photographing system comprises a button for instructing an execution of an image photographing process, a control unit for monitoring a depression of the button, and a timer. The control unit starts up the timer by setting a first count time  
10 upon detecting the depression of the button, and starts up the timer by further setting a second count time when the first count time has elapsed before the depressed button is released, and the image photographing process is executed after the second count time has elapsed.

15           This button may be a mechanical button and may also be a button, e.g., an icon displayed on a screen of a computer.

          Herein, the timer is a device for measuring a specified count time and informing of an elapse thereof. The timer may be of either an increment type in which a time value is incremented  
20 from 0 up to the specified count time, or a decrement type in which the specified count time is decremented down to 0.

          When the user depresses the button, the control unit starts up the timer by setting the first count time, and monitors whether or not the depressed button is released. In the case of executing  
25 the timer photographing, the user continues to depress the button. Thus, when the first count time elapses, the control unit starts up the timer by further setting the second count time. The second

09737588-121800

count time is a wait time for the timer photographing.  
Accordingly, the image photographing process is executed after  
the second count time has been elapsed.

On the other hand, the image photographing process may  
5 be executed immediately when the depressed button is released  
before the first count time elapses.

As explained above, according to the present invention,  
one button can be used in common for the normal photographing  
function of promptly conducting the photographing, and for the  
10 timer photographing function of performing the photographing  
after waiting till the predetermined time elapses. Further,  
with this construction, the number of components of the image  
photographing system can be decreased.

15 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view showing an external configuration of an  
image photographing system in an embodiment of the present  
invention;

FIG. 2 is a block diagram showing a hardware architecture  
20 of the image photographing system in the embodiment of the present  
invention;

FIG. 3 is a view showing how a timer display icon changes;  
and

FIG. 4 is a flowchart showing processes of a control  
25 program.



panel 203 may be a pressure sensitive type sensor, an electrostatic type sensor and an ultrasonic type sensor.

The device for detecting the position of the operation by the user is not, however, limited to this touch panel in terms of actualizing the present invention, and, as a matter of course, other devices such as a mouse, a keyboard etc are usable.

The touch panel 203 has an image display screen 21, a timer display icon 22 and a photographed image display frame module 23.

Normally, the latest image photographed by the image acquisition device 101 is displayed on the image display screen 21. This image is read in real time from the image acquisition device 101 to the portable terminal 200.

Further, the images, which have already been photographed and stored on the hard disk, are to be displayed on the image display screen 21.

The photographed image is reduced and displayed as an index image in the photographed image display frame module 23. When the user selects a desired index image by an operation on the touch panel 203, the selected index image is enlarged and displayed on the image display screen 21.

The timer display icon 22 serves to indicate whether in the process of timer photographing or normal photographing. FIG. 3 shows variations in display configuration of this icon. The timer display icon 22 is a circular button 22a in the normal photographing state. When in the timer photographing, the timer display icon 22 changes to a button 22b with a hour hand when



in the timer photographing, and is flickered. Further, the timer display icon 22 functions as a photography instruction button as a button 102 of the image acquisition device 101 functions.

FIG. 2 is a block diagram showing a hardware architecture of this image photographing system.

The image acquisition device 101 includes the button 102 for giving an instruction to execute the image photographing process and a lens 103, which are provided on a front surface of a body 100 thereof. The image acquisition device 101 has a CCD imaging device 104 incorporated into the body 100 thereof. The image acquisition device 101 is classified as a so-called CCD camera.

The lens 103 functions to form an image of a photographing object on the CCD imaging device 104 incorporated into the image acquisition device body 100. The image formed on the CCD imaging device 104 is transferred in real time to the portable terminal 200 via the USB cable 300.

The portable terminal 200 has inside a processing unit 201 for monitoring the button 102 and controlling the image acquisition device 101, a storage unit 202 for storing a control program executed by the processing unit 201 and data dealt with by the processing unit 201, and the touch panel 203 serving as a user interface.

The button 102 detects a user's depression on the button itself. Namely, when the button 102 is pressed down, an interruption occurs in the processing unit 201, and the button 102's being depressed is transferred to the processing unit 201.

The button also detects that the user releases the button 102. That is, when the button 102 is released from the depression, the interruption occurs in the processing unit 201, and the button 201's being released is transferred to the arithmetic unit 201.

5       The processing unit 201 executes the control program stored in the storage unit 202.

10       The processing unit 201 reads in real time data of the image formed on the CCD imaging device 104, and writes the image data to the storage unit 202. The image data written to the storage unit 202 are displayed on the image display screen 21 on the touch panel 203. Hence, the image momentarily changes on the image display screen 21.

15       Further, in a normal state, the processing unit 201 monitors the button 102 on the basis of an interruption processing function. To be specific, when the user depresses or releases the button 102, the processing unit 201 detects its operation in accordance with an unillustrated interruption processing program. If a depression time of the button 102 is less than a predetermined time T1 (corresponding to a first count time),  
20       the processing unit 201 executes a photographing process immediately after detecting the release of the button 102.

25       On the other hand, if the user continues to depress the button 102 over the predetermined time T1, the processing unit 201 sets a predetermined time T2 (corresponding to a second count time) and starts up a built-in timer. At this time, the processing unit 201 changes the timer display icon 22 to the button 23b with the hour hand. Further, the processing unit

201 flickers the button 23b with the hour hand and thus indicates that the timer has been started up. When the timer informs the processing unit 201 of an elapse of the predetermined time T2, the processing unit 201 executes the photographing process.

5 In the photographing process, the processing unit 201 stores the latest image data written in real time to the storage unit 202 in the unillustrated hard disk with a predetermined file name given to the same data. Further, the processing unit 201 creates an index image of this item of image data, and stores  
10 the storage unit 202 with the index image data together with the file name when the image data have been stored.

Note that this index image is displayed on the photographed image display frame module 23. When the user touches at the index image in a way of depressing it, the processing unit 201  
15 detects the depression through the touch panel 203. Then, the processing unit 201 searches a file name corresponding to this index image, and displays the image data thereof on the image display screen 21.

The storage unit 202 is constructed of a RAM (Random Access  
20 Memory). The storage unit 202 is stored with the control program executed and with the image data processed by the processing unit 201.

FIG. 4 shows the processes of the control program executed by the processing unit 201. The processing unit 201 normally  
25 monitors whether or not the button 102 is depressed (step 301, which will hereinafter simply referred to as 301) on the basis of the interruption processing function.

Upon detecting the depression of the button 102, the timer is initialized by setting the time T1 in order to count a time for which the button 102 is depressed (302). Till the timer informs the processing unit 201 of an elapse of the time T1 (till  
5 a Yes judgement is made in 303), the processing unit 201 monitors the release of the button 102 based on the interruption processing function (304).

Before the timer notifies of the elapse of the time T1, the button 102 is released (Yes in 304), the processing unit  
10 201 promptly executes the photographing process (305).

While on the other hand, if the notification of the elapse of the time T1 is given from the timer without releasing the button 102 (Yes in 303), the processing unit 201 boots again the timer by setting the time T2 (306). Further, the processing  
15 unit 201 flickers the timer display icon 22, thus indicating an on-execution of wait-for-time function by the timer.

In the meantime, the processing unit 201 monitors whether or not the button 102 is again depressed (307). Further, in parallel with this monitoring process, the processing unit 201  
20 waits information from the timer (308).

When the button 102 is again depressed before being notified of the elapse of the time T2 from the timer, the processing unit 201 returns again to 301 and monitors the depression of the button 102 on the basis of the interruption processing  
25 function (Yes in 307). This is because the re-depression of the button 102 implies an instruction to cancel the timer photographing.

Whereas if notified of the elapse of the time T2 from the timer without re-depressing the button 102 (Yes in 308), the processing unit 201 executes the photographing process (305).

After finishing the photographing, the processing unit  
5 201 goes again back to 301 and monitors the depression of the button 102 on the basis of the interruption processing function.

As discussed above, the image photographing system in this embodiment, if the button is released within the time T1 after the user has depressed the button 102, immediately executes the  
10 photographing, and, if the user continues to depress the button 102 over the time T1, carries out the timer photographing.

The image photographing system in this embodiment, if the button 102 is kept depressed for a long period of time, the timing of the photographing is delayed by the predetermined time.  
15 Further, the image photographing system in the present embodiment, if the button 102 is depressed for a short period of time, promptly performs the photographing. Thus, there exists an analogous relation between the delay time and the depressing time of the button 102, and hence the user is able to well familiarize with  
20 the operation of this image photographing system.

Downsizing is highly demanded of the portable terminal 200 described above and of the image acquisition device 101 connected to the personal computer etc. Accordingly, one single button 102 is used for the normal photographing and the timer,  
25 which is effective especially in the portable terminal 200 and the image acquisition device 101 connected to the portable terminal 200 that are required to be downsized.

<Modified Example of System>

The image photographing system in the embodiment discussed above is constructed by connecting the image acquisition device 101 to the portable terminal 200. The embodiment of the present invention is not, however, limited to this architecture. For example, the image photographing system may also be constructed by connecting the image acquisition device 101 to an unportable, i.e., so-called installation type computer substituting the portable terminal 200.

<Modified Example of Signal Medium>

In the embodiment discussed above, the image acquisition device 101 is connected via the USB cable 300 to the portable terminal 200. The embodiment of the present invention is not, however, confined to this architecture. A cable capable of transferring the data in parallel and an optical fiber cable may also be used in place of the USB cable 300.

Further, instead of their being connected via the cable, the image acquisition device 101 may have a light emitting unit, while the portable terminal 200 may have a light receiving unit, whereby the image is transferred through infrared-ray communications.

Moreover, the image acquisition device 101 may have a transmitter, while the portable terminal 200 may have a receiver, whereby the image is transferred on electromagnetic waves.

Furthermore, the present invention can be also embodied by such a configuration that the image acquisition device 101 is connected directly to the portable terminal 200 via an

interface card.

<Modified Example by Push Button on Screen>

The normal photographing and the timer photographing are set depending on a length of the depressing time of the button 102 provided on the image acquisition device 101 in the embodiment discussed above. The embodiment of the present invention is not, however, restricted to this mode. For instance, the timer display icon 22 displayed on the touch panel 203 may also be used as a substitute for the button 102. That is, the normal photographing and the timer photographing may be executed in a distinguishable manner from each other depending on a length of a depressing time of the timer display icon 22 by detecting a depression of the timer display icon 22.

<Application to Digital Camera>

In the embodiment discussed above, the image photographing system is constructed by connecting the image acquisition device 101 to the portable terminal 200 via the USB cable 300. The embodiment of the present invention is not, however, limited to this construction. For example, in a typical digital camera, the normal photographing and the timer photographing may be executed in the distinguishable manner depending on a length of a depressing time of a photographing button thereof.

The image acquisition device 101 including the CCD imaging device 104 is used in the embodiment described above. The embodiment of the present invention is not, however, limited to this construction. For instance, a MOS image sensor may also be used in place of the CCD imaging device 104.

<Modified Example of Depressing Mode>

5 The normal photographing and the timer photographing are executed in the distinguishable manner depending on the length of the depressing time of the button 102 in the embodiment discussed above. Instead of this mode, the normal photographing and the timer photographing may be executed in the distinguishable manner depending on how many times the button 102 is depressed. In this case, a count time of the timer may be changed corresponding to the number of the depressions of the button 102. For instance, the following mode may be taken. An operation of depressing the button 102 once instructs the normal photographing, an operation of consecutively depressing the button 102 twice instructs the photographing after 10 seconds, and an operation of consecutively depressing the button 102 three times instructs the photographing after 15 seconds.

<Readable-by-Computer Recording Medium>

20 The control program in this embodiment may be recorded on a readable-by-computer recording medium. Then, the computer connected to the image acquisition device 101 is made to read and execute the control program on this recording medium, and is thereby capable of functioning as the image photographing system demonstrated in the present embodiment.

25 Herein, the readable-by-computer recording medium embraces recording mediums capable of storing information such as data, programs, etc. electrically, magnetically, optically and mechanically or by chemical action, which can be all read by the computer. What is demountable out of the computer among



those recording mediums may be, e.g., a floppy disk, a magneto-optic disk, a CD-ROM, a CD-R/W, a DVD, a DAT, an 8mm tape, a memory card, etc.

Further, a hard disk, a ROM (Read Only Memory) and so on  
5 are classified as fixed type recording mediums within the computer.

<Data Communication Signal Embodied in Carrier Wave>

Furthermore, the control program may be stored in the hard disk and the memory of the computer, and downloaded to other  
10 computers via communication media. In this case, the program is transmitted as data communication signals embodied in carrier waves via the communication media. Then, the computer downloaded with this program can be made to function as the image photographing system in this embodiment.

15 Herein, the communication media may be classified into cable communication mediums (such as metallic cables including a coaxial cable and a twisted pair cable, or an optical communication cable), and wireless communication media (such as satellite communications, ground wave wireless  
20 communications, etc).

Further, the carrier waves are electromagnetic waves for modulating the data communication signals, or the light. The carrier waves may be, however, DC signals (in this case, the data communication signal takes base band waveform with no  
25 carrier wave). Accordingly, the data communication signal embodied in the carrier wave may be any one of a modulated broad band signal and an unmodulated base band signal (corresponding



WHAT IS CLAIMED IS:

1. A processing system comprising:

a timer; and

a control unit monitoring a button for instructing an  
5 execution of an image photographing process, starting up said  
timer if said button is depressed continuously for a  
predetermined time or longer, and executing the image  
photographing process after said timer has counted a  
predetermined time.

10

2. A processing system according to claim 1, wherein said  
control unit, if a depressing time of said button is less than  
the predetermined time, executes the image photographing process  
immediately after releasing said button from being depressed.

15

3. A processing system according to claim 1, wherein said  
button is provided on a connectable/disconnectable image  
acquisition device.

20

4. A processing system according to claim 1, wherein said  
button is an object displayed on a display device.

5. A processing system comprising:

a module detecting a depressing time of a button

25 instructing an execution of an image photographing process; and

a module changing a timing of executing the image  
photographing process after releasing said button from being

depressed on the basis of the depressing time of said button.

6. An image photographing system comprising:

a button instructing an execution of an image photographing

```
5 process;
```

a control unit monitoring a depression of said button;

and

a timer,

wherein said control unit starts up said timer by setting

10 a first count time upon detecting the depression of said button,  
and starts up said timer by further setting a second count time  
when the first count time has elapsed before the depressed button  
is released, and

the image photographing process is executed after the  
15 second count time has elapsed.

7. An image photographing system according to claim 6,  
wherein the image photographing process is executed immediately  
when the depressed button is released before the first count  
time elapses.

8. A storage medium readable by a machine tangible  
embodying a program of instructions executable by the machine  
to perform method steps comprising:

25        detecting a depression of a button for instructing to  
execute an image photographing process;

starting up a timer by setting a first count time after

detecting the depression of said button;

detecting a release of said button;

starting up said timer by further setting a second count  
time when the first count time elapses before said depressed  
5 button is released; and

executing the image photographing process after the second  
count time has elapsed.

9. A storage medium readable by a machine tangible  
10 embodying a program according to claim 8, of instructions  
executable by the machine, the method steps further comprising  
a step of executing the image photographing process immediately  
when said depressed button is released before the first count  
time elapses.

15

10. A storage medium readable by a machine tangible  
embodying a program of instructions executable by the machine  
to perform method steps comprising:

displaying, on a display device, a button of which a  
20 depression is detectable;

detecting a depression of said button;

starting up a timer by setting a first count time after  
detecting the depression of said button;

detecting a release of said button;

25 starting up said timer by further setting a second count  
time when the first count time elapses before said depressed  
button is released; and

executing the image photographing process after the second count time has elapsed.

11. A storage medium readable by a machine tangible  
5 embodying a program according to claim 10, of instructions executable by the machine, the method steps further comprising a step of executing the image photographing process immediately when said depressed button is released before the first count time elapses.

10

09777588-121800

## ABSTRACT OF THE DISCLOSURE

An image photographing system in which one button is used in common for a function of prompt photographing and a function of photographing after a predetermined time has elapsed,

5 comprises a button for instructing an execution of an image  
photographing process, a control unit for monitoring a depression  
of this button, and a timer. The control unit starts up the  
timer by setting a first count time upon detecting the depression  
of the button, and starts up the timer by further setting a second  
10 count time when the first count time has elapsed before the  
depressed button is released, and the image photographing process  
is executed after the second count time has elapsed.

FIG.1






FIG.2






FIG.3



[illegible]

## Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

IMAGE PHOTOGRAPHING SYSTEM HAVING

TIMER FUNCTION, AND MEDIUM

上記発明の明細書（下記の欄でx印がついていない場合は、本表に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を \_\_\_\_\_ とし、  
 （該当する場合） \_\_\_\_\_ に訂正されました。

☐ was filed on \_\_\_\_\_  
 as United States Application Number or  
 PCT International Application Number  
 \_\_\_\_\_ and was amended on  
 \_\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

00737588-121800

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration  
(日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一ヶ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

## Prior Foreign Application(s)

外国での先行出願

2000-43660

(Number)  
(番号)

Japan

(Country)  
(国名)(Number)  
(番号)(Country)  
(国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)  
(出願番号)(Filing Date)  
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)  
(出願番号)(Filing Date)  
(出願日)(Application No.)  
(出願番号)(Filing Date)  
(出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに仮定になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような虚偽による虚偽の表明を行なえば、出願した、又は共に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

21/02/2000

(Day/Month/Year Filed)  
(出願年月日)(Day/Month/Year Filed)  
(出願年月日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)  
(出願番号)(Filing Date)  
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Japanese Language Declaration (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許審判局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, P-41,455 and William M. Schertler, 35,348 (agent)

書類送付先

Send Correspondence to:

STAAS & HALSEY  
700 Eleventh Street, N.W.  
Suite 500  
Washington, D.C. 20001

直接電話連絡先 (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY  
(202) 434-1500

|             |    |   |                   |
|-------------|----|---|-------------------|
| 唯一または第一発明者名 |    | Full name of sole or first inventor   |                   |
|             |    | Yutaka SAITO  |                   |
| 発明者の署名      | 日付 | Inventor's signature  | Date              |
|             |    | <i>Yutaka Saito</i>   | November 30, 2000 |
| 住所          |    | Residence   |                   |
|             |    | Kawasaki, Japan   |                   |
| 国籍          |    | Citizenship   |                   |
|             |    | Japanese  |                   |
| 私書箱         |    | Post Office Address   |                   |
|             |    | c/o FUJITSU LIMITED, 1-1,<br>Kamikodanaka 4-chome, Nakahara-ku,<br>Kawasaki-shi, Kanagawa, 211-8588 Japan |                   |
| 第二共同発明者     |    | Full name of second joint inventor, if any  |                   |
| 第二共同発明者     |    | Second inventor's signature   | Date              |
|             |    |   |                   |
| 住所          |    | Residence   |                   |
|             |    |   |                   |
| 国籍          |    | Citizenship   |                   |
|             |    |   |                   |
| 私書箱         |    | Post Office Address   |                   |
|             |    |   |                   |

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)